



**Weyn-Lauwers** N.V.

Industriepark-Noord 12  
B - 9100 SINT-NIKLAAS

Tel. : 00 32 (0)3 776.34.13  
Fax : 00 32 (0)3 778.09.52  
weynlauwers@weynlauwers.be  
www.weynlauwers.be

**diaphragm tank  
membrane tank  
SPT V/H**



**OMSCHRIJVING**

**SPT V / H**

pressured water tanks with membrane  
preset pressure 2 bar  
temp. -10°C + 90°C  
food quality & safety butyl membrane

max. pressure 10/16 bar

<b>M</b>	<b>type</b>	<b>volume</b>	<b>L-H</b>	<b>diam.</b>
1"	SPT V 60.10	60 L - V - 10bar	815	380
1"	SPT H 60.10	60 L - H - 10bar	650	380
1"	SPT V 80.10	80 L - V - 10bar	790	450
1"	SPT H 80.10	80 L - H - 10bar	640	450
1/2" & 1"	SPT V 100.10	100L - V - 10bar	910	450
1/2" & 1"	SPT V 100.16	100L - V - 16bar	915	464
1/2" & 1"	SPT H 100.10	100L - H - 10bar	750	450
1/2"-6/4"	SPT V 200.10	200L - V - 10bar	1215	554
1/2"-6/4"	SPT V 200.16	200L - V - 16bar	1220	556
1/2"-6/4"	SPT H 200.10	200L - H - 10bar	1020	554
1/2"-6/4"	SPT V 300.10	300L - V - 10bar	1375	625
1/2"-6/4"	SPT H 300.10	300L - H - 10bar	1190	625
1/2"-6/4"	SPT V 500.10	500L - V - 10bar	1460	775
1/2"-6/4"	SPT V 750.10	750L - V - 10bar	1925	790
1/2" - 2"	SPT V 1000.10	1000L - V - 10bar	1915	935