


Weyn-Lauwers N.V.

Industriepark-Noord 12
B - 9100 SINT-NIKLAAS

Tel. : 00 32 (0)3 776.34.13
Fax : 00 32 (0)3 778.09.52
weynlauwers@weynlauwers.be
www.weynlauwers.be

MOTOREN voor kogelkranen en vlinderkleppen



J+J

huis : kunststof

temp. : -20°C +70°C

IP 65

4 eindschakelaars

anti-condensatieweerstand



type L20	12-48VDC/15-48VAC	max.25Nm	9,5 sec/90°
type H20	85-240VAC/VDC	max.25Nm	9,5 sec/90°
type L55	12-48VDC/15-48VAC	max.60Nm	10 sec/90°
type H55	85-240VAC/VDC	max.60Nm	11 sec/90°
type L140	12-48VDC/15-48VAC	max.170Nm	31 sec/90°
type H140	85-240VAC/VDC	max.170Nm	31 sec/90°
type L300	12-48VDC/15-48VAC	max.350Nm	66 sec/90°
type H300	85-240VAC/VDC	max.350Nm	66 sec/90°



SA05

230VAC - 24VAC/VDC 12VDC
50 Nm 17 sec/90° IP67



SA05 PCU

met 4-20 mA positioner
230VACV/24VAC/VDC
50 Nm 17 sec/90° IP67



SA05-RBP

met battery pack
230VAC
50 Nm 17 sec/90° IP67



huis : aluminium - temp. : -20°C +70°C - 4 eindschakelaars - anti-condensatieweerstand



SR met veerterugbrenging IP67

230VAC

SR05	50 Nm	17 sec/90°
SR10	100 Nm	20 sec/90°
SR20	200 Nm	50 sec/90°



NA IP67

230VAC 3x400VAC 24VAC/VDC

NA06	60 Nm	17 sec/90°
NA09	90 Nm	17 sec/90°
NA15	150 Nm	20 sec/90°
NA28	280 Nm	24 sec/90°
NA38	380 Nm	24 sec/90°
NA60	600 Nm	29 sec/90°
NA100	1000 Nm	29 sec/90°
Na150	1500 Nm	87 sec/90°
NA200	2000 Nm	87 sec/90°
NA250	2500 Nm	87 sec/90°
NA09 PCU	90 Nm	17 sec/90°
NA15 PCU	150 Nm	20 sec/90°
NA09 RBP	90 Nm	17 sec/90°
NA15 RBP	150 Nm	20 sec/90°

NAX ATEX II 2 EExd II B T4 - (1&2)

230VAC

NAX06
NAX09
NAX15
NAX28
NAX38
NAX60



met 4-20 mA positioner
met 4-20 mA positioner
met battery pack
met battery pack

