



Weyn-Lauwers N.V.

Industriepark-Noord 12
B - 9100 SINT-NIKLAAS

Tel. : 00 32 (0)3 776.34.13
Fax : 00 32 (0)3 778.09.52
weynlauwers@weynlauwers.be
www.weynlauwers.be

KNIFE GATE VALVES

Knife gate valves

for fluids concerned by risk category III, H module of 97/23/CE directive N°0062
Unidirectional tightness (sense of mounting) - flanged PN10



fig 380

DN 50 - DN 700

- GG25 body - non-rising handwheel
- Stainless steel 304 gate - NBR gasket / max. temp 80°C
- fig 380M with metal seat max 160°C

fig 380I

DN 50 - DN 400

- CF8M - 1.4408 body - non-rising handwheel
- Stainless steel 316 gate - EPDM gasket / max. temp 110°C

fig 381

DN 50 - DN 400

- GG25 body - double acting pneumatic actuator
- Stainless steel 304 gate - NBR gasket / max. temp 80°C
- fig 381M with metal seat max 160°C

fig 381I

DN 50 - DN 400

- CF8M - 1.4408 body - double acting pneumatic actuator
- Stainless steel 316 gate - EPDM gasket / max. temp 110°C

fig 382

DN 50 - DN 400

- GG25 body - electric actuator
- Stainless steel 304 gate - NBR gasket / max. temp 80°C
- fig 382M with metal seat max 160°C

fig 382I

DN 50 - DN 300

- CF8M - 1.4408 body - electric actuator
- Stainless steel 316 gate - EPDM gasket / max. temp 110°C

OPTIONS

- mechanical limit switches
- inductive position indicators
- solenoid valve 5/2 monostable
- filters - regulators - lubricators
- throttle valves with silencer
- silencer
- air tank for normally closed action
- deflector
- lever set
- spare seat :
 - + NBR
 - + EPDM
 - + FKM (viton)
 - + PTFE (teflon)

