



Weyn-Lauwers N.V.

INDUSTRIEPARK-NOORD 12
B - 9100 SINT-NIKLAAS

TEL. 0032 (0)3 776.34.13
FAX. 0032 (0)3 778.09.52

weynlauwers@weynlauwers.be
www.weynlauwers.be

BRANDSTOFSLANGEN VERSTERKT

FUELFLEX

FUELFLEX

versterkte slang uit PVC nitril voor doorvoer van mazout e.d.



BESTELNR	DIAMETER mm	GEWICHT/M gr/m	WD bar	LENGTE m	
350036	4 - 8	48	10	50	
	6,3 - 11	80	10	50	
	8 - 14	130	10	25 - 50	
	10 - 16	150	10	25 - 50	
	12 - 19	210	10	25 - 50	
	15 - 23	290	10	25 - 50	
	20 - 28	370	8	25 - 50	
	25 - 32	425	8	25 - 50	
	30 - 39	600	8	25 - 50	

CARBORUB

CARBORUB

versterkte mazoutslang in rubber



	DIAMETER mm	GEWICHT/M gr/m	WD bar	LENGTE m	
	19 - 29	550	10	40	
	25 - 36	750	10	40	

AUTO-CONDUCT

AUTO-CONDUCT

rubber benzineslang met opgevacuiseerde, hittewerende textielomvlechting
temp. : -30 tot 100 °C



	DIAMETER mm	GEWICHT/M gr/m	WD bar	LENGTE m	
	6 - 11	90	15	20	
	8 - 13	110	15	20	
	10 - 15	145	5	25	